



WG4005B

Wireless 802.11g Gateway with Printer Server

Built-in Printer Server

Easy to install

Advanced Firewall

UPnP

Allows home or SOHO users to share broadband Internet connection, files and printers throughout the home/office.

Wireless 802.11g Cable/DSL Broadband Router is the industry's first 802.11g router with built-in printer server. With this router, you can share a single printer to all PC's connected to the network. It is a multi-functional router which combines a 4-port switch, a high speed 802.11g wireless access point, an SPI firewall and a USB1.1 Printer Server in one single device. The WG4005B router is a perfect networking solution for home and business users that is looking for a simple, all-in-one network product.

Wireless 802.11g Gateway with Printer Server also provides network security and management features for users. Network Address Translation (NAT), Dynamic Host Configuration Protocol (DHCP), advanced packet filtering with hacker attack monitor, logging and Stateful Packet Inspection (Firewall-SPI), Universal Plug and Play (UPnP), Dynamic DNS (TZO DDNS), WiFi Protected Access (WPA), 802.1x + TKIP, and wireless to wired Ethernet bridging are all supported.

KEY BENEFITS

- Router function - shares Internet connection through wired/wireless
- USB1.1 Printer Server
- Secured wireless connections with WPA, 802.1x + TKIP
- Setup Wizard ;V easy installation
- Advanced firewall with SPI



WG4005B

802.11g Wireless Gateway with Printer Server

SPECIFICATIONS

- Standards IEEE802.3, IEEE802.3u, IEEE802.11g, IEEE802.11b
- Channels 11 Channels (US, Canada)
13 Channels (Europe)
14 Channels (Japan)
- Ports WAN: One 10/100 RJ45 WAN port
LAN: Four 10/100 RJ45 LAN ports
One Power Supply
One Reset Button
One USB1.1 Printer Server
- LEDs PWR, WLAN, WAN, LAN1, LAN2, LAN3, LAN4, Printer Server
- Transmitted Power 17dBm
- Software Features NAT, DHCP Client/Server, DNS Relay, Dynamic DNS, SNTP, Stateful Packet Inspection (SPI) Firewall VPN Passthru-IPSEC, PPTP, L2TP
- Security WEP, Wi-Fi Protected Access (WPA), MAC Address Filtering

Environmental

- Dimensions 130 x 85 x 32 mm
- Power 9V, 1.25 A
- Operating Temperature 0 ~ 55 oC
- Storage Temperature -20~70 oC
- Humidity 15% ~ 95%
- Certifications FCC, CE, WiFi

Arcadyan Technology Corporation

TAIWAN Headquarters

4F, No.9, Park Avenue II, Science-based Industrial Park , Hsinchu
300 Taiwan, R.O.C
Tel : +886.3.578.7000
Fax: +886.3.563.7326
Fax: +886.3.563.7327

China

63, No. 421, Hong Cao Road
Shanghai, 200233 P.R. China
Tel: +86.21.6485.9922
Fax: +86.21.6495.7924

USA

1362 Borregas Avenue
Sunnyvale, CA 94089
Tel: +1.408.548.9930
Fax: +1.408.747.1091

© 2004 Arcadyan Technology Corporation. All rights reserved. The information and specifications are subject to change without prior notice. Arcadyan tries to ensure that all information in this document is correct but does not accept liability for any error or omission.

Wi-Fi is a trademark of the Wireless Ethernet Compatibility Alliance, Inc. Windows and Windows Me are registered trademark of Microsoft Corporation. All other trademarks are the property of their perspective owners.

